

# Material Safety Sheet

## 安全检验报告

MSD No. Hot melt 001

### PRODUCT & COMPANY IDENTIFICATION

[Product Name]: HOT MELT GLUE

[产品名称]: 热熔胶

[COMPANY IDENTIFICATION] 公司认证

SUPPLIER: 供应商

NAME: YOUXIN ENTERPRISE (ZHONGSHAN) ADHESIVE CO.LTD

名称: 有行企业(中山)胶类制品有限公司

ADDRESS: INDUSTRY ZONE, SOUTH OF ROAD, SEHNWAN TOWN, ZHONGSHAN CITY, GUANGDONG, CHINA

地址: 中国广东省中山市神湾镇大道南

TEL: +86-760-6601502 /6600017 FAX: +86-760-660007 /6600019

EMERGENCY CONTACT 紧急联络方式

Please call the telephone number above.

请联系以上电话即可

MANUFACTURE 厂商

NAME: YOUXIN ENTERPRISE (ZHONGSHAN) ADHESIVE CO.LTD

名称: 有行企业(中山)胶类制品有限公司

ADDRESS: INDUSTRY ZONE, SOUTH OF ROAD, SEHNWAN TOWN, ZHONGSHAN CITY, GUANGDONG, CHINA

地址: 中国广东省中山市神湾镇大道南

TEL: +86-760-6601502 /6600017 FAX: +86-760-660007 /6600019

### 1. COMPOSITION INFORMATIONS ON HARMFUL INGREDIENT 产品组分

Properties:(特性) ;

1. Appearance: 外观 -----white /yellow
2. soft point °C: 软化点-----≥88
3. viscosity of hot melt (Pa.s)黏度----- ≥13
4. Solidification time (second)固化时间-----68
5. Temperature(°C) 温度-----150/165
6. Tension N/CM 拉伸力-----≥295
7. Remover tension 扭矩- N/CM ----- ≥25

### 2. Packing:

PE Bag packing in Carton. 25 KG/CTN

### 3. Precautions 注意事项

#### 4.1 Safety 安全

Danger: The hot melt glue must be used at about 195°C. In case of reaching by mistake a temperature above 250°C.

危险: 必须在195°C左右的温度下使用, 避免温度错误的达到250°C。

#### 4.1.1 Prevention 预防措施

To avoid any contact of skin with melt glue. 避免皮肤与热熔胶的接触

The working place shall have an air exhaust 操作的地方必须保持通风

#### 4.1.2 Injuries 伤害

Contact with skin: burn 皮肤的接触: 烧伤

#### 4.1.3 First aid 注意事项

● In case of burnt skin, put under flowing water during a minimum of 5mn: do not try to tear out the glue.

- 如果烧伤皮肤, 在五分钟之内放入水中清洗, 不要用力拿掉粘在皮肤上的胶。
- In case of large burnt surface, do not try to clean or tear out the glue but call the doctor immediately.
- 如果大面积的烧伤到表面, 切勿用力私自去掉表面粘在皮肤上的胶, 请立即联系医生。

### 4.2 Handling

Store in chemicals room in cold environment, avoid of the sunshine. And keep out of children.

储存在干燥阴凉处, 避免日光照射。

### 5. FIRE FIGHTING MEASURE 防火措施

EXTINGUISHING MEDIA Suitable extinguishing media: Foam, Dry powder or carbon dioxide

灭火工具 适用的灭火工具为: 泡沫, 干粉或者二氧化碳灭火器

SPECIAL FIRE-FIGHTING PROCEDURES:

Do not direct a stream of water into hot burning pools. This may cause splash and increase fire density.

Use self-contained breathing apparatus and protective clothing.

不要直接用水来扑灭火焰, 这样容易扩大火焰

使用氧气头盔以及保护衣服

END OF DOCUMENT

YOUXING ENTERPRISE (ZHONGSHAN) ADHESIVE CO., LTD.

有行企业(中山)胶类制品有限公司

FANGXUOXING